



HB120-S

Dry bath

Features:

- A wide range of temperature control up to 120°C
- Timer function support is available
- Various types of optional blocks are available
- Overheating protection
- Lid for protection and heat preservation



Specifications

| | HB120-S |
|------------------------------|-----------------------------|
| Functions | Heating |
| Temperature range | Room temp.~120°C |
| Temperature control accuracy | ± 0.5°C |
| Temperature uniformity | ± 0.5°C |
| Max heating rate | 5.5°C/min |
| Timer | 1min~99h59min |
| Screen | LED |
| Overheating protection | 140°C |
| Adapter block material | aluminum |
| Voltage, Frequency | 100~120V/220~240V,50Hz/60Hz |
| Power | 160W |
| Dimension[WxDxH] | 95x150x50mm |
| Weight | 3kg |

| Cat.No. | Block types | Capacity | Diameter Depth |
|--|-------------|---------------------------------|-------------------|
| 18900218 | | 0.2mLx54 | 6.4mm 15mm |
| 18900219 | | 0.5mLx40 | 8.2mm 26.4mm |
| 18900253 (1.5ml) 18900220 (2ml) | | 1.5mLx40 2mLx40 | 11mm 34.7mm |
| 18900221 | | 5/15mLx28 | 17mm 48mm |
| 18900222 | | 50mLx8 | 29.8mm 48mm |
| 18900224 | | 0.2mL+0.5mL+1.5/2mL 18+18+18 | - |
| 18900223 | | 96 or 384 well plate | - |



Adapter block selection



Overheating protection



Timer



LED display

