

The Thermo Mix series allow for precise and efficient heating and mixing, as well as excellent temperature accuracy and uniformity, offering a wide range of applications, such as gene synthesis, gene purification, gene and protein denaturation, enzymatic reaction, bacterial growth, etc.



HCM100-Pro

Thermo Mix

HM100-Pro

Thermo Mix with heating

Features:

- Excellent mixing result
- Stable and wide range of speed adjustment
- Precise temperature control for heating and cooling
- Flexible adapter selection
- Programmable
- Compatible with various tubes



Blocks self recognition



Specifications

	HCM100-Pro	HM100-Pro
Functions	Heating, cooling & mixing	Heating&mixing
Temperature range	Heating: room temp. ~ 100°C Cooling: room temp. ~ below room temp. 15°C	Heating: room temp. ~ 100 °C
Temperature control accuracy[@ 20–45°C]	± 0.5°C	± 0.5°C
Temperature uniformity[@ 20–45°C]	Max ± 0.5 °C	Max ± 0.5 °C
Max. heating rate	5.5°C/min	5.5°C/min
Max. cooling rate	5 °C /min(110°C-room temp.) 0.5 °C/min(below room temp.)	-
Mixing frequency	300~1500rpm	300~1500rpm
Mixing orbit	3mm	3mm
Screen	TFT	TFT
Program	9	9
Overheating protection	150°C	150°C
Adapter block material	aluminum	aluminum
Voltage, Frequency	100–240V,50/60Hz	100–240V,50/60Hz
Power	200W	200W
Dimension[W×D×H] (without the heating block)	200×235×120mm	200×235×120mm
Weight	7.3kg	7.3kg