

DYNEO DD-1001F Refrigerated/Heating Circulator

New temperature control technology for demanding applications

DYNEO DD refrigerated circulators have a wide working temperature range. Refrigerated circulators are suitable for both internal and external applications. The multilingual 3.5-inch color display and unique rotary knob provide for straightforward and intuitive operation. Pump capacity is 22 l/min with pressure of 0.6 bar. The cooling machines operate precisely and reliably even at elevated ambient temperatures up to +40 °C.

Your advantages

- Powerful cooling machines
- Suitable for internal and external applications
- Optimized cooling coil design saves space in the bath tank
- Powerful and infinitely adjustable pressure pump
- Flow rate 22 l/min, pressure 0.6 bar
- Easy switching between internal and external circulation
- Large color TFT display, multilingual interface
- Central rotary knob (controller) simplifies operation
- Integrated programmer
- Integrated external Pt100 connection
- USB port
- RS232 interface or analog interfaces (optional)
- Bath cover included with delivery
- Integrated drain makes emptying liquid easy and safe.



Technical Data

Order No.	9021708						
Order No. with RS232 Option	9021708.D						
Order No. with analog Option	9021708.A						
Model series	DYNEO						
Category	Refrigerated - Heating Circulators						
Working temperature range (°C)	-30 ... +100						
Temperature control	PID						
Temperature stability (°C)	±0.01						
Setting / display resolution	0.01 °C						
Temperature Display	3.5" TFT Display						
Heating capacity (kW)	2						
Cooling capacity (Medium Ethanol)	°C	20	10	0	-10	-20	-30
	kW	1	0.95	0.85	0.6	0.32	0.12
Pump capacity flow rate (l/min)	8 ... 23						
Pump capacity flow pressure (bar)	0.1 ... 0.6						
Viscosity max. (cSt)	50						

Bath opening / bath depth (W x L / D cm)	35 x 41 / 30
Pump connections	M16x1
Barbed fittings diameter (inner dia. / mm)	8 / 12
Filling volume liters	42 ... 56
Refrigerant stage 1	R452A
Filling volume refrigerant stage 1 (g)	170
Global Warming Potential for R452A	2140
Carbon dioxide equivalent stage 1 (t)	0.364
Digital interface	USB
Analog connection input / output	Optional
Ambient temperature	5...40 °C
Dimensions W x L x H (cm)	45 x 64 x 95
Weight (kg)	73.7
Included with each unit	2 each barbed fitting for tubing 8 and 12 mm inner dia. (pump connections M16x1 male)
Bath tank	Stainless steel
Bath cover	integrated
Cooling of compressor	Air
Available voltage versions	200-230V/50-60Hz