

Magnetic Stirrers



MS-PA

LED Digital Magnetic Stirrer

Features:

- Digital speed control with a range of 100~1500rpm
- Max. stirring quantity of H₂O at 3L
- LED display shows speeds
- ABS housing provides a good performance of chemical resistance

MS-PB

Magnetic Stirrer

Features:

- A wide range of 0~1500rpm
- Max. stirring quantity of H₂O at 3L
- ABS housing provides a good performance of chemical resistance



Chemical resistance



Strong magnetism



LED display

Specifications

	MS-PA	MS-PB
Work plate Dimension	∅135(5 inch)/mm	∅135(5 inch)/mm
Work plate material	ABS	ABS
Motor type	DC motor	DC motor
Motor input power	5W	5W
Motor output power	3W	3W
Power	15W	10W
Voltage	100~120/200~240V,50/60Hz	100~120/200~240V,50/60Hz
Stirring positions	1	1
Max. stirring quantity[H ₂ O]	3L	3L
Max. magnetic bar[length]	50mm	50mm
Speed range	100~1500rpm	0~1500rpm
Speed display	LED	Scale
Protection class	IP42	IP42
Dimension [W x D x H]	150x260x80mm	150x260x80 mm
Weight	1.8kg	1.8kg
Permissible ambient temperature and humidity	5~40°C,80%	5~40°C,80%